



MONTCLAIR

GENERAL NOTES - STREETS

CITY OF MONTCLAIR - ENGINEERING DIVISION

City of Montclair 5111 Benito Street, Montclair, CA 91763 Tel: (909) 625-9440 Fax: (909) 621-1584

1. All work shall conform to the "Standard Specifications for Public Works Construction (Greenbook)", 2006 edition (including the latest supplemental amendments thereto). City standard drawings, to the extent that they are available, may be used. In lieu of City standard drawings, the "Standard Plans for Public Works Construction", 1997 edition (including the latest supplemental amendments thereto) may be used. All work shall be performed and completed to the satisfaction of the City Engineer or his appointed representative.
2. The approximate locations of known existing underground utilities are shown on this plan. The utilities are plotted from record and field data. The engineer assumes no liability as to the exact location of said lines whether shown or not shown on the plans. The contractor is to notify all utility companies prior to work or excavation to determine the exact locations of underground lines.
3. Streets may be required to have a seal coat applied at the option of the city engineer or appointed representative. Type of seal coat is to be determined by the City Engineer or his appointed representative.
4. Existing striping shall be removed and replaced as necessary. New striping and pavement markings shall be installed in accordance with the striping plan approved by the City Engineer or his appointed representative. Curb installations at less than 0.50 percent grade shall have construction stakes set at 12½ feet maximum intervals and all curb forms shall be checked for grade compliance prior to concrete pour. Maximum deviation from design profile grade at any location shall be 0.01 ft.
5. Sections 4216 and 4217 of the Government Code require a Dig Alert Identification Number be issued before the permit will be valid. For your Dig Alert ID number, call Underground Service Alert (toll free) at 1-800-227-2600 two working days before you dig.
6. The final pavement or surface layer of asphaltic concrete roadway pavement shall not be placed until all utilities and utility laterals within the roadway have been installed, compacted, tested, and accepted by the City; all on-site improvements including all grading, landscaping, and irrigation have been completed; and all roadway improvements are removed and replaced to the satisfaction of the City.
7. Contractor shall comply with and be solely liable for all applicable NPDES requirements.